

RT Series (0.8Ah - 28Ah)

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal	Maximum Discharge Current (A)	Maximum Charge Current (A)	Internal Resistance (mΩ)
		20hr	10hr	5hr	Length	Width	Height	Total Height					
RT445	4	4.5	4.3	3.8	48	48	102	108	0.5	F1	45	1.35	12
RT490	4	9.0	8.6	7.7	102	44	95	101	0.96	F1 / F2	90	2.7	10
RT495	4	9.5	9.0	8.1	102	44	95	101	1	F1 / F2	95	2.85	8
RT610	6	1.0	1.0	0.9	50	42	50	56	0.28	F1	10	0.3	50
RT612	6	1.2	1.1	1.0	97	24	52	58	0.32	F1	12	0.36	50
RT623	6	2.3	2.2	2.0	43	37	76	76	0.34	T5	23	0.69	50
RT628	6	2.8	2.7	2.4	66	33	98	104	0.6	F1	28	0.84	25
RT632	6	3.2	3.0	2.7	134	34	61	67	0.7	F1	32	0.96	25
RT635	6	3.5	3.3	3.0	134	34	61	67	0.75	F1	35	1.05	22
RT636	6	3.2	3.0	2.7	194	25	62	62	0.67	T1	18	1.08	32
RT642	6	4.2	4.0	3.6	70	47	101	107	0.72	F1	40	1.2	33
RT642S	6	4.2	4.0	3.6	70	47	103	105	0.72	T6	40	1.2	33
RT645	6	4.5	4.3	3.8	70	47	101	107	0.74	F1	45	1.35	23
RT645S	6	4.5	4.3	3.8	70	47	103	105	0.74	T6	45	1.35	23
RT655	6	5.5	5.2	4.7	70	47	101	107	0.85	F1	50	1.5	20
RT660	6	6.0	5.7	5.1	70	47	101	107	0.9	F1	60	1.8	18
RT660S	6	6.0	5.7	5.1	85	48	101	105	1.08	F1	60	1.8	20
RT670	6	7.0	6.7	6.0	151	34	94	100	1.1	F1 / F2	70	2.1	12
RT680	6	8.0	7.6	6.8	151	34	94	100	1.2	F1 / F2	70	2.1	12
RT680S	6	8.0	7.6	6.8	99	56	118	119	1.8	F1 / F2	80	2.4	15
RT6100	6	10	9.5	8.5	151	50	94	100	1.65	F1 / F2	100	3	9
RT6120	6	12	11.4	10.2	151	50	94	100	1.8	F1 / F2	120	3.6	8
RT6140	6	14	13.3	11.9	108	71	141	141	2.37	T8	140	4.2	10
RT1208	12	0.8	0.8	0.7	96	25	61	61	0.37	T9	8	0.24	250
RT1212	12	1.2	1.1	1.0	97	43	52	58	0.61	F1	12	0.36	95
RT1219	12	1.9	1.8	1.6	177	35	61	67	0.83	F1	19	0.57	55
RT1216C	12	1.6	1.5	1.4	143	24	65	65	0.6	T10	20	0.6	110

RT1220C	12	2.0	1.9	1.7	182	24	62	62	0.71	T10	23	0.69	100
RT1220M	12	2.0	1.9	1.7	151	20	89	89	0.68	T11	20	0.6	90
RT1222	12	2.2	2.1	1.9	104	46	75	81	1.2	F1	22	0.66	60
RT1222S	12	2.2	2.1	1.9	104	46	70	70	1.2	T19	22	0.66	65
RT1223	12	2.3	2.2	2.0	178	35	61	67	0.99	F1	23	0.69	50
RT1226	12	2.6	2.5	2.2	70	47	98	104	0.9	F1	26	0.78	55
RT1228	12	2.8	2.7	2.4	105	48	70	70	1	T16	28	0.84	35
RT1228S	12	2.8	2.7	2.4	67	67	97	103	1.1	F1	28	0.84	45
RT1229	12	2.9	2.8	2.5	80	56	99	105	1.1	F1	29	0.87	45
RT1232	12	3.2	3.0	2.7	135	67	60	66	1.3	F1	32	0.96	45
RT1235	12	3.5	3.3	3.0	135	67	60	66	1.43	F1	35	1.05	40
RT1242	12	4.2	4.0	3.6	90	70	101	107	1.4	F1 / F2	40	1.2	40
RT1245	12	4.5	4.3	3.8	90	70	101	107	1.45	F1 / F2	45	1.35	38
RT1250	12	5.0	4.8	4.3	90	70	101	107	1.6	F1 / F2	50	1.5	35
RT1250S	12	5.5	5.2	4.7	140	48	102	104	1.7	T14	50	1.35	25
RT1255	12	5.5	5.2	4.7	90	70	101	107	1.7	F1 / F2	55	1.56	35
RT1270	12	7.0	6.7	6.0	151	65	94	100	2.15	F1 / F2	70	2.1	25
RT1275	12	7.5	7.1	6.4	151	65	94	100	2.35	F1 / F2	72	2.16	25
RT1280	12	8.0	7.6	6.8	151	65	94	100	2.35	F1 / F2	80	2.4	25
RT1290B	12	9.0	8.6	7.7	151	65	94	100	2.45	F2	90	2.7	14
RT1290	12	9.0	8.6	7.7	151	65	94	100	2.6	F2	90	2.7	18
RT1290S	12	9.0	8.6	7.7	151	65	111	117	2.75	T7	90	2.7	18
RT1295	12	9.5	9.0	8.1	151	65	94	100	2.8	F2	95	2.85	15
RT12100	12	10	9.5	8.5	151	98	95	101	3.2	F2	100	3	15
RT12100S	12	10	9.5	8.5	151	65	111	117	3.25	F2	100	3	20
RT12120	12	12	11.4	10.2	151	98	95	101	3.6	F2	12	3.6	16
RT12140	12	14	13.3	11.9	151	98	95	101	4.2	F2	140	4.2	12
RT12170	12	17	16.2	14.5	181	77	167	167	5.2	F3 / F13	170	5.1	14
RT12180	12	18	17.1	15.3	181	77	167	167	5.3	F3 / F13	180	5.4	14
RT12200	12	20	19.0	17.0	181	77	167	167	5.9	F3 / F13	200	6	12
RT12260	12	26	24.7	22.1	175	166	125	125	8.6	F3 / F13	260	7.8	10
RT12280	12	28	26.6	23.8	175	166	125	125	9.2	F3 / F13	280	8.4	9
RT12280S	12	28	26.6	23.8	165	126	174	174	10	F17 / F11	280	8.4	9

RA Series (33Ah - 240Ah)

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal		Maximum Discharge Current	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	3hr	1hr	Length	Width	Height	Total Height		Bolt & Nut	Insert			
RA6-100	6	100	75	65	194	170	205	210	16.5	_____	F14 (M8)	500	30	2
RA6-150	6	150	113	98	260	180	247	252	23.5	_____	F12 (M8)	750	45	2
RA6-200	6	200	150	130	322	178	226	247	30	F16 (M8)	F14 (M8)	1000	60	4
RA6-200S	6	200	150	130	260	180	247	252	30	_____	F12 M8	1000	60	4
RA6-225S	6	225	169	146	243	188	276	296	32	F16 M8	F14 M8	1125	67.5	4
RA6-225	6	225	169	146	322	178	226	247	32	F16 (M8)	F14 (M8)	1125	67.5	4
RA12-33	12	33	25	21	196	130	163	180	10.2	F7 (M6)	F11 (M6)	165	9.9	9
RA12-40	12	40	30	26	197	165	169	169	13.5	F4 (M5)	F11 (M6)	200	12	8
RA12-45	12	45	34	29	197	165	169	169	14	F4 (M5)	F11 (M6)	225	13.5	8
RA12-55	12	55	41	36	229	138	210	229	18	F15 (M6)	F11 (M6)	275	16.5	6
RA12-60	12	60	45	39	259	169	210	228	20.5	F15 (M6)	F11 (M6)	300	18	6
RA12-65	12	65	49	42	350	167	179	182	21	F5 (M8)	F11 (M6)	325	19.5	6
RA12-68	12	68	51	44	350	167	179	182	22.2	F5 (M8)	F11 (M6)	325	19.5	6
RA12-70	12	70	53	46	350	167	179	182	23	F5 (M8)	F11 (M6)	350	21	6
RA12-70S	12	70	53	46	259	169	210	228	23	F15 (M6)	F11 (M6)	350	21	6
RA12-75	12	75	56	49	259	169	210	228	23.5	F15 (M6)	F11 (M6)	375	22.5	6
RA12-80	12	80	60	52	350	167	179	182	24	F5 (M8)	F11 (M6)	400	24	5.5
RA12-90	12	90	68	59	307	169	211	229	28.5	F15 (M6)	F12 (M8)	450	27	5.2
RA12-100	12	100	75	65	328	172	222	222	30	F5 (M8)	F12 (M8)	500	30	5
RA12-100S	12	100	75	65	307	169	211	229	32	F15 (M6)	F12 (M8)	500	30	4.8
RA12-120	12	120	90	78	409	177	225	225	36	F5 (M8)	F12 (M8)	600	36	4.5
RA12-120S	12	120	90	78	328	172	222	222	32	F5 (M8)	F12 (M8)	600	36	4
RA12-134	12	134	101	87	341	173	280	285	41.5	_____	F12 (M8)	600	36	4
RA12-145	12	145	109	94	341	173	280	285	44	_____	F12 (M8)	600	36	4
RA12-160	12	160	120	104	341	173	280	285	50	_____	F12 (M8)	600	36	4
RA12-150	12	150	113	98	483	170	241	241	45	F5 (M8)	F12 (M8)	750	45	4

RA12-200	12	200	150	130	522	240	219	240	60	F16 (M8)	F12 (M8)	1000	60	4
RA12-225	12	225	169	146	522	240	219	240	65	F16 (M8)	F12 (M8)	1125	67.5	3.8
RA12-240	12	240	180	156	522	240	219	240	66.5	F16 (M8)	F12 (M8)	1200	72	3.8
RA12-260	12	260	215	169	520	268	220	225	73.5	F16	F14 M8	1000	75	4

RL Series (2V50Ah - 3000Ah)

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal	Maximum Discharge Current (A)	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	3hr	1hr	Length	Width	Height	Total Height					
RL2-100	2	100	81	65	171	72	226	230	6.5	F10	500	20	1.0
RL2-150	2	150	122	98	171	101	208	228	8	F10	750	30	0.85
RL2-200	2	200	162	130	171	106	327	368	15	F10	1000	40	0.8
RL2-300	2	300	243	195	171	151	327	368	20	F10	1500	60	0.75
RL2-400	2	400	324	260	171	210	327	368	27	F10	2000	80	0.7
RL2-500	2	500	405	325	171	241	327	368	32	F10	2500	100	0.67
RL2-600	2	600	486	390	175	302	327	368	41	F10	3000	120	0.63
RL2-800	2	800	648	520	175	411	327	368	57	F10	3000	160	0.6
RL2-1000	2	1000	810	650	175	479	327	368	65	F10	4000	200	0.55
RL2-1500	2	1500	1220	980	352	407	338	383	100	F10	4000	300	0.5
RL2-2000	2	2000	1620	1300	349	490	338	383	132	F10	4000	400	0.4
RL2-3000	2	3000	2430	1950	351	712	338	383	201	F10	4000	600	0.3

AGM Deep Cycle Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal		Maximum Discharge Current	Maximum Charge Current (A)	Internal Resistance (mΩ)
		20hr	2hr	1hr	Length	Width	Height	Total Height		Bolt & Nut	Insert			
RT2445D	24	4.5	3.7	2.9	206	77	74	74	3.0	T17	—	45	1.4	60
RT2470D	24	7.0	5.8	4.6	302	65	102	102	5.3	T17	—	45	2.1	40
RT24120D	24	14	12	9.1	300	98	102	102	8.5	T17	—	45	4.2	30
RT36120D	36	12	10	7.8	190	151	115	115	10.2	T24	—	80	3.6	50
RT1250D	12	5.5	4.6	3.6	90	70	101	107	1.9	F1	F2	50	1.5	30
RT1270D	12	8.0	6.6	5.2	151	65	94	100	2.5	F1	F2	70	2.1	18

RT1280D	12	8.0	6.6	5.2	116	86.5	101	101	2.6	T20	——	40	2.4	25
RT1290D	12	10	8.3	6.5	151	65	111	117	2.8	F1	F2	90	2.7	18
RT12120D	12	14.5	12.0	9.4	151	98	95	101	4.2	F2	——	120	3.6	12
RT12180D	12	18	14.9	11.7	181	77	167	167	5.3	F3	F13 (M5)	150	4.5	17
RT12200D	12	20	16.6	13.0	181	77	167	167	6.2	F3	F13 (M5)	200	6.0	14
RT12260D	12	28	23	18.2	175	166	125	125	9.2	F3	F13 (M5)	260	7.8	10
RA6-100D	6	100	75	65	194	170	205	210	16.8	——	F14 M8	500	30	2
RA6-150D	6	150	113	98	260	180	247	252	24	——	F12 M8	750	45	2
RA6-200D	6	200	150	130	322	178	226	247	30.5	F16 M8	F14 M8	1000	60	4
RA6-200SD	6	200	150	130	260	180	247	252	30.5	——	F12 M8	1000	60	4
RA6-225D	6	225	169	146	322	178	226	247	32.6	F16 M8	F14 M8	1125	67.5	4
RA6-225SD	6	225	169	146	243	188	276	296	32.5	F16 M8	F14 M8	1125	67.5	4
RA12-33D	12	33	27	21.5	196	130	163	180	10.2	F7	F11 (M6)	165	9.9	9
RA12-40D	12	40	33	26	197	165	169	169	13.5	F4	F11 (M6)	200	12.0	8
RA12-45D	12	45	37	29	197	165	169	169	15.0	F4	F11 (M6)	225	13.5	8
RA12-55D	12	55	46	36	229	138	210	229	18.0	F15	F11 (M6)	275	16.5	6
RA12-65D	12	65	54	42	350	167	179	182	22.2	F5	F11 (M6)	325	19.5	6
RA12-75D	12	75	62	49	259	169	210	228	23.5	F15	F11 (M6)	375	22.5	6
RA12-80D	12	80	66	52	350	167	179	182	24.0	F5	F11 (M6)	400	24	5.5
RA12-90D	12	90	75	59	307	169	211	229	28.5	F15	F12 (M8)	450	27	5.2
RA12-100D	12	100	83	65	328	172	222	222	32.0	F5	F12 (M8)	500	30	5
RA12-120D	12	120	100	78	409	177	225	225	38.0	F5	F12 (M8)	600	36	4
RA12-134D	12	134	101	87	341	173	280	285	41.5	——	F12 (M8)	600	36	4
RA12-145D	12	145	109	94	341	173	280	285	44	——	F12 (M8)	600	36	4
RA12-150D	12	150	125	98	483	170	241	241	47.0	F5	F12 (M8)	750	45	4
RA12-200D	12	200	166	130	522	240	219	240	65.0	F16	F12 (M8)	1000	60	4
RA12-230D	12	230	191	150	522	269	203	208	66.0	F16	F12 /M8	1000	60	4
RA12-260D	12	260	215	169	520	268	220	225	74.0	F16	F14 M8	1000	75	4

High Rate Discharge Series

Model	Voltage (V)		Rating Power (W)			Dimension (mm)				Weight (Kg)	Terminal		Maximum Discharge Current	Maximum Charge Current (A)	Internal Resistance (mΩ)
			15m	5m	3m	Length	Width	Height	Total Height		Faston	Insert			
RT645H	6	5.00	52	116	145	70	47	101	107	0.8	F2	—	45	1.35	20
RT650H	6	5.50	57	128	160	70	47	101	107	0.9	F2	—	50	1.5	18
RT670H	6	8.00	84	186	232	151	34	94	100	1.2	F2	—	70	2.1	10
RT680H	6	8.50	89	197	247	151	34	94	100	1.4	F2	—	70	2.1	10
RT1245H	12	5.00	104	232	290	90	70	101	107	1.6	F2	—	45	1.35	35
RT1250H	12	5.50	115	255	319	90	70	101	107	1.7	F2	—	50	1.5	30
RT1250SH	12	5.50	115	255	319	140	48	102	104	2.0	T14	—	50	1.5	25
RT1270H	12	7.50	157	348	435	151	65	94	100	2.4	F2	—	70	2.1	18
RT1280H	12	9.00	188	418	522	151	65	94	100	2.6	F2	—	80	2.4	18
RT1290H	12	9.50	198	441	551	151	65	94	100	2.8	F2	—	90	2.7	18
RT12100SH	12	11.50	240	534	667	151	65	111	117	3.25	F2	—	100	3	18
RT12120H	12	14.00	292	650	812	151	98	95	101	4.3	F2	—	120	3.6	12
RT12260H	12	28.00	585	1299	1624	175	166	125	125	9.5	F3	F13 (M5)	260	7.8	8
RA12-75H	12	80.00	1670	3712	4640	260	169	210	235	24.5	F15	F11 (M6)	800	30	5
RA12-90H	12	100.00	2088	4640	5800	307	169	211	216	32	F15	F12 (M8)	1000	30	5
RA12-100H	12	110.00	2297	5104	6380	328	172	222	222	32	F5	F12 (M8)	1000	30	5
RA12-120H	12	130.00	2714	6032	7540	407	177	225	225	38	F5	F12 (M8)	1000	30	5
RA12-150H	12	155.00	3236	7192	8990	483	170	240	240	47	F5	F12 (M8)	1000	30	5
RA12-200H	12	210.00	4385	9744	12180	522	240	219	240	62.5	F16	F12 (M8)	1000	30	5

Front Terminal Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal	Maximum Discharge Current (A)	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	3hr	1hr	Length	Width	Height	Total Height					
RA12-55F	12	55	41	36	277	106	223	223	18	F11	275	16.5	6
RA12-90F	12	90	68	59	563	114	188	188	24	F6	375	22.5	5.8
RA12-105F	12	105	79	68	508	111	236	236	32.5	F8	525	31.5	5

RA12-110F	12	110	83	72	394	110	286	286	32	F9	500	30	5
RA12-120F	12	120	90	78	551	109	239	239	36	F9	500	30	5
RA12-150F	12	150	113	98	552	110	287	287	45	F9	750	45	4
RA12-160F	12	160	120	104	552	110	287	287	49.5	F9	750	45	4
RA12-170F	12	170	128	111	552	110	287	287	51	F9	750	45	4
RA12-180F	12	180	135	117	560	125	316	316	54	F9	750	45	4

Electric Vehicle Battery

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal	Maximum Charge Current (A)	Internal Resistance (mΩ)
		20hr	2hr	1hr	Length	Width	Height	Total Height				
RT12120EV	12	14	12	9.1	151	98	95	101	3.9	F2	3.6	12
RT12140EV	12	14	12	9.1	151	98	95	101	4.2	F2	3.6	12
RT12220EV	12	22	18	14.3	181	77	167	167	6.2	F3	6	14
RT12240EV	12	24	20	15.6	183	79	167	167	7.2	T23	6	10
RT12240EVX	12	24	20	15.6	181	77	167	170	7.2	F18	6	10

12V GEL Standby Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal		Maximum Discharge Current	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	5hr	1hr	Length	Width	Height	Total Height		Bolt & Nut	Insert			
RT12240G	12	24	17	14	175	166	125	125	8.6	F3	F13 (M5)	240	4.8	12
RT12260G	12	26	19	16	175	166	125	125	9.4	F3	F13 (M5)	260	5.2	10
RT12280SG	12	28	22	17	165	126	174	174	10.2	F17	F11	280	5.6	10
RA12-33G	12	33	28	21	196	130	163	172	10.5	F7 (M6)	F11 (M6)	330	6.6	9
RA12-40G	12	40	31	24	198	166	171	171	13.8	F4 (M5)	F11 (M6)	400	8	9
RA12-55G	12	55	39	35	229	138	210	215	18.5	F15 (M6)	F11 (M6)	275	11	8
RA12-65G	12	65	52	39	350	167	179	179	23	F5 (M8)	F11 (M6)	325	13	8
RA12-75G	12	75	58	45	259	169	210	215	25	F15 (M6)	F11 (M6)	375	15	8
RA12-80G	12	80	64	48	350	167	179	179	25	F5 (M8)	F11 (M6)	400	16	6
RA12-90G	12	90	71	54	307	169	211	216	31	F15 (M6)	F12 (M8)	450	18	5.5
RA12-100G	12	100	80	60	328	172	217	222	33	F5 (M8)	F12 (M8)	500	20	5
RA12-100SG	12	100	72	62	307	169	211	229	32	F15 (M6)	F12 (M8)	500	20	5

RA12-120G	12	120	86	74	409	177	225	225	39	F5 (M8)	F12 (M8)	600	24	4.5
RA12-120SG	12	120	86	74	328	172	222	222	37	F5 (M8)	F12 (M8)	600	24	4.5
RA12-134G	12	134	96	84	341	173	280	285	41.5	_____	F12 (M8)	670	27	4
RA12-145G	12	145	104	91	341	173	280	285	44	_____	F12 (M8)	725	29	4
RA12-150G	12	150	108	93	483	170	241	241	48	F5 (M8)	F12 (M8)	750	30	4
RA12-160G	12	160	115	101	341	173	280	285	50	_____	F12 (M8)	800	32	4
RA12-200G	12	200	144	124	522	240	219	224	63	F16 (M8)	F12 (M8)	1000	40	4
RA12-230G	12	230	166	143	522	269	203	208	66	F16 (M8)	F12 (M8)	1000	46	4
RA12-260G	12	260	215	169	520	268	220	225	74.5	F16	F14 M8	1000	50	4

6V GEL Standby Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal		Maximum Discharge Current	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	3hr	1hr	Length	Width	Height	Total Height		Bolt & Nut	Insert			
RA6-100G	6	100	72	62	194	170	205	210	17.5	_____	F14 (M8)	500	20	5
RA6-150G	6	150	109	94	260	180	247	252	24.5	_____	F12 (M8)	750	30	4
RA6-200G	6	200	146	125	322	178	226	247	31.2	F16 (M8)	F14 (M8)	1000	40	4
RA6-200SG	6	200	145	125	260	180	247	252	32	_____	F12 M8	1000	60	4
RA6-225G	6	225	162	141	322	178	226	247	34	F16 M8	F14 M8	1125	45	4
RA6-225SG	6	225	162	141	243	188	276	296	34	F16 M8	F14 M8	1125	45	4

2V GEL Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal	Maximum Discharge Current (A)	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	5hr	1hr	Length	Width	Height	Total Height					
RL2-100G	2	100	77	61	171	72	226	230	6.8	F10	500	20	1.0
RL2-150G	2	150	116	93	171	101	208	228	8.5	F10	750	30	1.2
RL2-200G	2	200	154	123	171	106	327	368	15.4	F10	1000	40	1.1
RL2-300G	2	300	231	184	171	151	327	368	20.8	F10	1500	60	0.8
RL2-400G	2	400	308	246	171	210	327	368	27.6	F10	2000	80	0.8
RL2-500G	2	500	385	307	171	241	327	368	32.4	F10	2500	100	0.72

RL2-600G	2	600	462	369	175	302	327	368	41.8	F10	3000	120	0.7
RL2-800G	2	800	616	492	175	411	327	368	57.6	F10	3000	160	0.68
RL2-1000G	2	1000	770	615	175	479	327	368	65.4	F10	4000	200	0.6
RL2-1500G	2	1500	1159	927	352	407	338	383	101	F10	4000	300	0.6
RL2-2000G	2	2000	1539	1230	349	490	338	383	133	F10	4000	400	0.5
RL2-3000G	2	3000	2309	1845	351	712	338	383	202	F10	4000	600	0.4

Front Terminal GEL Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal	Maximum Discharge Current (A)	Maximum Charge Current (A)	Internal Resistance (mΩ)
		10hr	3hr	1hr	Length	Width	Height	Total Height					
RA12-55FG	12	55	40	34	277	106	223	223	19	F11	275	11	8
RA12-90FG	12	90	76	65	563	114	188	188	25	F8	450	18	6
RA12-105FG	12	105	79	68	508	111	236	236	33.5	F9	525	21	7
RA12-110FG	12	110	85	72	394	110	286	286	33	F9	550	22	5
RA12-120FG	12	120	88	76	551	109	239	239	37	F9	600	24	5
RA12-150FG	12	150	108	93	552	110	287	287	47	F9	750	30	5
RA12-160FG	12	160	115	101	552	110	287	287	50.6	F9	800	32	4.5
RA12-170FG	12	170	122	158	552	110	287	287	52	F9	800	34	4
RA12-180FG	12	180	128	112	560	125	316	316	55	F9	900	36	4

GEL Deep Cycle Series

Model	Voltage (V)	Capacity (Ah)			Dimension (mm)				Weight (Kg)	Terminal		Maximum Discharge Current	Maximum Charge Current (A)	Internal Resistance (mΩ)
		20hr	2hr	1hr	Length	Width	Height	Total Height		Bolt & Nut	Insert			
RT12180DG	12	18	13	11	181	77	167	167	6.5	F3	F13 (M5)	180	3.6	14.2
RT12260DG	12	26	19	17	175	166	125	125	9.6	F3	F13 (M5)	260	5.2	11
RT12280DG	12	28	21	18	175	166	125	125	10.2	F3	F13 (M5)	280	5.6	11
RA6-100DG	6	100	72	62	194	170	205	210	18.5	_____	F14 M8	500	20	5
RA6-150DG	6	150	109	94	260	180	247	252	25.5	_____	F12 M8	750	30	4

RA6-200DG	6	200	146	125	322	178	226	247	32.5	F16 M8	F14 M8	1000	40	4
RA6-200SDG	6	200	145	125	260	180	247	252	32.5	_____	F12 M8	1000	60	4
RA6-225DG	6	225	162	141	322	178	226	247	34.6	F16 M8	F14 M8	1125	45	4
RA6-225SDG	6	225	162	141	243	188	276	296	34.5	F16 M8	F14 M8	1125	45	4
RA12-33DG	12	33	24	21	196	130	163	172	11.2	F7 (M6)	F11 (M6)	330	6.6	9.5
RA12-40DG	12	40	30	25	197	165	169	169	13.5	F4 (M5)	F11 (M6)	200	8	9
RA12-55DG	12	55	41	35	229	138	210	215	18.7	F15 (M6)	F11 (M6)	275	11	8.6
RA12-65DG	12	65	48	41	350	167	179	179	23.5	F5 (M8)	F11 (M6)	325	13	8
RA12-75DG	12	75	56	47	259	169	210	215	25.4	F15 (M6)	F11 (M6)	375	15	7
RA12-80DG	12	80	59	50	350	167	179	179	26.5	F5 (M8)	F11 (M6)	400	16	6
RA12-90DG	12	90	67	57	307	169	211	216	31.7	F15 (M6)	F12 (M8)	450	18	6
RA12-100DG	12	100	74	63	328	172	217	222	33.5	F5 (M8)	F12 (M8)	500	20	5
RA12-100HDG	12	100	74	63	307	169	211	229	34.2	F15 (M6)	F12 (M8)	500	20	5
RA12-120DG	12	120	89	76	409	177	225	225	39.5	F5 (M8)	F12 (M8)	600	24	5
RA12-120HDG	12	120	89	76	328	172	222	222	34	F5 (M8)	F12 (M8)	600	24	5
RA12-134DG	12	134	99	84	341	173	280	285	42	_____	F12 (M8)	670	26	5
RA12-145DG	12	145	107	91	341	173	280	285	44.5	_____	F12 (M8)	725	29	5
RA12-160DG	12	160	118	101	341	173	280	285	50.5	_____	F12 (M8)	800	32	5
RA12-150DG	12	150	111	95	483	170	241	241	48.6	F5 (M8)	F12 (M8)	750	30	4
RA12-150HDG	12	150	111	95	483	170	241	241	47.2	F5 (M8)	F12 (M8)	750	30	4
RA12-200DG	12	200	148	126	522	240	219	224	63.8	F16 (M8)	F12 (M8)	1000	40	4
RA12-200HDG	12	200	148	126	522	240	219	224	64.8	F16 (M8)	F12 (M8)	1000	40	4
RA12-230DG	12	230	170	145	522	269	203	208	67	F16 (M8)	F12 (M8)	1000	46	4
RA12-260DG	12	260	215	169	520	268	220	225	75.0	F16	F14 M8	1000	50	4

Remark:

S: Special

M: Medical

C: Camcorder Use

D: Deep Cycle

H: High Rate Discharge

F: Front Terminal

EV: Electric Vehicle Battery

G: GEL Type